# MILLCREEK SPREADER SPECIFICATIONS
# PTO DRIVE MODELS


Model 57


Model 77


Model 77XL


Model 97


Model 97XL

| Heaped Capacity (ASAE S324.1) | Approx. Equivalent Wheel-Barrow Loads * | Body and Overall Dimensions | Approx. Unladen Weight (standard model) | Recomended Min. Tractor HP | STANDARD EQUIPMENT & AVAILABLE OPTIONS | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | Clevis Hitch (Drop Pin Hitch) | Pick Up Hitch 'Ring' Eye | Jack Stand | Endgate | Fines Pan | Upper Beater |
| 1.58 m3 (56 cu ft) | 9 | 0.94m (3' 1"), 1.57m (5' 2"), 0.44m (1' 5"), 2.28m (7' 6"), 3.50m (11' 6"), 0.86m (2' 10") | 340 Kg | 20 HP | Std. | Opt. | Std. | Opt. | Opt. | Opt. |
| 2.04 m3 (72 cu ft) | 12 | 0.94m (3' 1"), 1.57m (5' 2"), 0.44m (1' 5"), 2.89m (9' 6"), 4.11m (13' 6"), 0.86m (2' 10") | 376 Kg | 22 HP | Std. | Opt. | Std. | Opt. | Opt. | Opt. |
| 2.63 m3 (93 cu ft) | 15 | 1.12m (3' 7"), 1.57m (5' 2"), 0.67m (2' 2"), 2.89m (9' 6"), 4.11m (13' 6"), 1.12m (3' 7") | 448 Kg | 24 HP | Std. | Opt. | Std. | N/A | Opt. | Std. |
| 3.08 m3 (109 cu ft) | 18 | 1.4m (4' 7"), 2.03m (6' 8"), 0.44m (1' 5"), 2.89m (9' 6"), 4.11m (13' 6"), 0.99m (3' 3") | 573 Kg | 25 HP | Std. | Opt. | Std. | Opt. | Opt. | Opt. |
| 3.96 m3 (140 cu ft) | 24 | 1.55m (5' 1"), 2.03m (6' 8"), 0.67m (2' 2"), 2.89m (9' 6"), 4.11m (13' 6"), 1.22m (4') | 655 Kg | 30 HP | Std. | Opt. | Std. | N/A | Opt. | Std. |

** Assumes typical large 170 litre (6 cu ft) wheelbarrow.*
*Always ensure that your Millcreek spreader is operable safely within the limits of your tow vehicle, as specified by the vehicle manufacturer. Specifications may be subject to change without notice.* *© Meadow Machinery Ltd. 2014*

*Available throughout the EU exclusively from:*

Meadow Machinery
**Tel** +44 (0)1652 679000 **Email** info@millcreek.co.uk
**www.millcreek.co.uk**